# The Construction of Deep and Complex Basements and underground structures within extremely difficult urban environment

(Part 1)

by Raymond W M Wong

# Examples of underground structures include:

- Basement of buildings
- Semi-basement with slope stabilization purpose
- Transport facilities such as railway station, tunnel and pedestrian subway
- Access or services shaft


#### Attributes that affect the construction of deep basement:

- 1. Size of a site
- 2. Volume of work
- 3. Shape and Typographical conditions of site
- 4. Neighbourhood conditions of a site
- 5. Geotechnical conditions
- 6. Internal layout of the basement or other related structures
- 7. Availability of resources for the project
- 8. Availability of expertise skill
- 9. Appropriateness of the methods selected for the construction
- 10. Special performance requirements imposed

Under the built-environment of Hong Kong, a basement often may have other factors that make the work more complex, such as:

- working under very fast-track schedule.
- The location of the structure in extremely congested built-up area.
- Close to existing structures with potential hazards like old buildings,
- busy roadways, elevated carriageways, slopes or retaining structures.
  Close to sensitive underground facilities like the main drain, utility trenches, vehicular underpasses, pedestrian subways, or a metro line.
- Located in close proximity to a river bank, sea wall or harbour-front.
- Requiring to carry out several construction activities at the same time within the site. In some cases works like site formation, slope work, foundation, basement construction, or even part of the super-structures may be required to be carried out at the same.
- Sometimes, even a new basement is required to construct simultaneously to replace an old one

This situations will create very difficult coordination problems that involve various contractors and complicate the contractual position of the entire job.



Examples of projects – working in close proximity of sensitive and unstable slope- the case of Hollywood Plaza


Basement Project in very congested urban environment – the Redevelopment of Kwong On Bank in Queen's Road Central, Central District, Hong Kong






# Examples of very difficult environment for constructing a substructure - Work in close proximity to seawall





### Work in close proximity to seawall




## Work in close proximity to seawall



Examples of very difficult environment for constructing a substructure - Work in extremely small site







#### Complicated soil support arrangement









Large-scale basement project involved very complex phasing planning










Site formation, slope work and basement construction work at the same time under carefully planned phasing arrangement










Complicated phasing arrangement in constructing a basement – demolition of the old basement and construct the new basement at the same time (Lee Garden Hotel redevelopment)



Demolish the old basement before construction of the new one – the case of Cheung Kong Center (former Hilton Hotel redevelopment)



#### The case of AIA HQ building redevelopment in Stubbs Road









The new basement structure under construction within rows of strut frame





#### Cheung Kong Center - Foundation and Basement construction arrangement

A 60m diameter cofferdam lined with 1m-thick diaphragm wall was provided for the construction of the building core in advance. The cofferdam would be removed when constructing the basement structure











The Center - Foundation and Basement construction arrangement



#### The Center - Foundation and Basement construction arrangement




The main structure of The Center uprising from the cofferdam pit. The basement on the side was constructed afterward using top-down approach




Complicated surrounding environment as seen in the TST East Station – underpinning to a section of pedestrian subway













Example of a servicing shaft providing access point usually from ground to work area deep below









## Common managerial problems identified in the construction of deep basement:

- 1. -Very expensive and time consuming in nature, often involved huge amount of work resources.
- 2. -Inconsistent and sensitive to the quality of planning and management of individual projects.
- 3. -Works are highly hazardous, both to human operatives working within and the life and properties of third parties that within the vicinity.
- 4. -Works involved a lot of managerial challenges. Such as, in the preparation of a highly efficient working programme, monitoring and rectifying the progress of works in case problems arising, or in resources planning where materials, labours & plant equipment are involved.






A temporary retaining wall for the Nicoll Highway MRT project under construction collapsed (2004)



There are many methods to construct large-scaled and deep basement/underground structures

- -Deep basement can be constructed using some traditional ways such as cut & fill or bottom up methods. These methods are relatively economical and effective when dealing with certain jobs which are
- simpler in nature.
  2. -On the other hand where basement is going deeper and the surrounding environment getting more complex and sensitive, top-down or combined method may be a more appropriate option to construct.







Open-cut followed by top-down method to construct the MTR Kowloon Station







## An extremely large-scale and complex project – Central Reclamation in 1995



## An extremely large-scale and complex project – Construction of the International Finance Centre Phase II

(Top-down for the podium portion and bottom up for the building core portion)










An extremely large-scale and complex project – Construction of Terminus for HK Express Rail (combination of open-cut, bottom-up and top-down)






















An extremely large-scale and complex project – Construction of Terminal 2 building in CLK (combination of open-cut, bottom-up and top-down)






An extremely large-scale and complex project – Re-Construction of Terminal 2 building in CLK (demolition of existing T2, later combination of open-cut, bottom-up and top-down to construct the new structure)



















































Examples of very complicated phasing arrangement during the basement construction – Sky City in Chek Lap Kok









